

GO2 ENT

Versions



<p>Go2 Ent- Plus 1 Go2 screen remote control (dual camera)</p>	<ul style="list-style-type: none"> • Including remote control with screen • Dual backup communication links: <ul style="list-style-type: none"> • The main communication frequency 5.8G telemetry telemetry all the way to the image of the digital transmission of an integrated signal transmission; • The backup communication frequency all-netcom 4G • Video transmission: image 1080P high-definition picture, latency as low as 180ms, support for standard network port video streaming input, while supporting dual-channel 1080P high-definition video signal transmission • Explosion-proof with screen, support for full network pass 4G network • Standard image sensing system: dual camera resolution 1080P wide angle 120 °, equipped with four lights high brightness fill light • Does not contain depth camera, can not be individually optional servo robot arm / lidar, etc.
<p>Go2 Ent-Plus 2 Go2 screen remote control (dual camera+three in one)</p>	<ul style="list-style-type: none"> • Including remote control with screen • Dual backup communication links: <ul style="list-style-type: none"> • The main communication frequency 5.8G telemetry telemetry all the way to the image of the digital transmission of an integrated signal transmission; • The backup communication frequency all-netcom 4G • Video transmission: image 1080P high-definition picture, latency as low as 180ms, support for standard network port video streaming input, while supporting dual-channel 1080P high-definition video signal transmission • Explosion-proof with screen, support for full network pass 4G network • Standard image sensing system: dual-camera resolution 1080P wide angle 120 °, equipped with four lights high brightness fill light • Searchlight system: power 30W, brightness 3000 lumens • Warning light system: a variety of police light mode, police light color (red, blue), power 10W • Digital voice broadcasting system: digital coding and decoding transmission, the maximum propagation distance of the sound of the speaker is 500~800m, the • Function: <ul style="list-style-type: none"> • Real-time shouting, recording upload, audio playback, text-to-speech, lighting burst flash, lighting constant light, lighting brightness adjustment, red and blue burst flash, red and blue burst flash mode switching" • Depth camera is not included, not separately optional servo robotic arm / radar, etc.
<p>Go2 Ent-Plus 3 Go2 screen remote control (dual camera+6 38mm transmitters)</p>	<ul style="list-style-type: none"> • With all the functions of Go2 remote control with screen (dual camera) • Six-channel 38mm launcher mode: electronic trigger mode. Material: aviation aluminum + carbon fiber, etc. • With laser aiming system support ammunition: 38mm electric firing smoke, tear gas, explosive shells, etc. • Mounting: Fixed / fast folding structure. Manually adjustable angle of 0° - 90 °. • Control: App (with screen controller) • Depth camera is not included, can not be individually equipped with mechanical arm / radar, etc.
<p>Go2 Ent-Plus 4 Go2 screen remote control (dual camera+capture net gun launcher)</p>	<ul style="list-style-type: none"> • Equipped with all functions of Go2 screen remote control (dual camera) • Capture method of the net launcher: electronic trigger mode • Material: Aviation aluminum, etc. Equipped with laser assisted aiming system • Effective range: 8-10m; Net area: 9 square meters • Installation method: Quick detachable structure • Control method: App (with screen remote control) • Does not include depth cameras and cannot be separately equipped with servo mechanical arms/radars, etc
<p>Go2 Ent-Plus 5 Go2 screen remote control (dual camera+dual gimbal)</p>	<ul style="list-style-type: none"> • Including remote control with screen • Dual backup communication links: <ul style="list-style-type: none"> • TBD • Depth camera is not included, not separately optional servo robotic arm / radar, etc.
<p>Go2 Ent-U6</p>	<ul style="list-style-type: none"> • Go2 (gas detection) • Excluding screen mounted remote control (dual camera), including two handed remote control. Go2 Standard Luggage Non Go2 Industry Series Special Packaging Boxes • Control method: Two handed remote control and Go2 official app. The gas detection interactive interface is integrated into the official Go2 APP • Temperature measurement: -40~70°C with an accuracy of ± 1°C (ambient temperature of 25°C) • Humidity measurement: 0-100% accuracy ± 3% • Oxygen measurement: measurement range 0-30%, accuracy ± 3% • Carbon monoxide measurement: measurement range 0~1000ppm ± 3% • Carbon dioxide measurement: measurement range 0-20ppm ± 3% • Methane measurement: measurement range 0~100%, accuracy ± 3% • Hydrogen sulfide measurement: measurement range 0~100ppm ± 3% • Benzene measurement: measurement range 0~100ppm ± 3% • Interface types: Ethernet interface and 458 interface • Excluding depth cameras